М.А.Т. Namık Elal Caddesi 21 Yelki 35310 Izmir Turkey T: 90 232 236 79 90 F: 90 232 236 79 94 info@mat.com.tr www.mat.com.tr

M.A.T. 1010 IRC 10.10 m racer cruiser

Specification

January 2021

Туре

10.15 m dual purpose yacht aimed at providing competitive IRC performance and comfortable accommodation

Design

Mills Yacht Design, Mark Mills Fox Engineering, John Fox ISAF certified compliance with International Standard ISO 12215 www.sailing.org/sailors/plan-review-certificates.php

Design Category

CE category A10

Dimensions			
Length overall	10.15 m	I	13.60 m
Hull length	10.15 m	J	3.82 m
LWL	8.75 m	Р	13.40 m
Beam max	3.32 m	E	4.63 m
Draft	2.10 m	STL	4.56 m
Displacement	4250 kg		
Ballast	2150 kg		
Fuel tank	56		
Fresh Water tank	100 I		

Construction

Hull , deck and bulkheads produced with vacuum assisted resin infusion technology (VAI) in PVC foam cored vinylester/e-glass NPG acid gelcoat color: RAL 9010, others on request Molded nonskid on deck and cockpit floor Composite structural liner for interior arrangement Light composite interior components in cored polyester/e-glass

Keel

550 kg SG iron fin with 1600 kg lead/antimony bulb = 2150 kg (approximate) Recessed in the hull and bolted to structural composite frame Coated and faired with a layer glass/epoxy

Rudder and Steering

Composite rudder and carbon fiber stock Jefa high performance self-aligning top/lower rudder bearings Tiller steering or composite twin wheel steering on request

Deck

Primary winches: 2 x Harken radial B40.2 STA self-tailing 2 speed alloy winches

Halyard winches: 2 x Harken radial B35.2 STA self-tailing 2 speed alloy winches

Winches for 2:1 mainsheet on request

Harken Black Magic block and car package including: Windward sheeting mainsheet traveller and track Longitudinal jib tracks, cars and purchase system Mainsheet purchase blocks Spinnaker sheet and deflector blocks Foreguy blocks Halvard lead blocks Folding pad eyes

Spinlock XTS series rope clutches on centerline Custom alloy fairleads 4 opening BSI moonlight coach roof portlights

Custom tempered glass coach roof windows on request 2 opening BSI moonlight portlights in cockpit 1 opening Lewmar round foredeck hatch Portlights interior trims in anodized alloy Molded toe rail to mast Composite black stanchions, pulpits and pushpits 4 mm S/S lifelines, 620 mm high Custom stainless steel chainplates recessed in hull Recessed companionway sliding hatch Plastimo 135 mm compass

Mast and Rig

Composite mast collar Alloy mast with 2 sets of aft swept spreaders Alloy racing boom with internal outhaul purchase Carbon fiber mast and boom on request Carbon fiber spinnaker pole Carbon fiber bow sprit on request Rod rigging Composite T5 backstay Long stroke integral hydraulic backstay adjuster Solid mechanical vang Lopolight combined LED navigation lights/anchor light on mast 1 main halyard sheave 1 CI I height jib halyard sheave 1 wing spinnaker/jib halyard sheave to spectacle at I height 2 masthead spinnaker halyard sheaves 1 pole lift sheave Engine Yanmar 22 Hp diesel engine with sail drive Yanmar 30 Hp engine on request

Engine panel recessed in the cockpit for protection Fresh water cooling Sea water filter Exhaust with muffler and water trap 56 I diesel tank Shut off valve between the diesel tank and the engine, diesel filter with water separator Diesel fill on deck 2 bladed folding propeller Teleflex single lever engine control

Electrical

12 volt DC 12 volt 60 A alternator on engine Deka 1x90 amp hour group 27 deep cycle house battery Deka 1x70 amp hour group 24 starter battery BSS main DC panel with house, engine and emergency switches 12 volt DC distribution panel with automatic circuit breakers Voltmeter 12 volt DC plug LED interior lights

Plumbing

100 I flexible fresh water tank Jabsco pressurized water system S/S hand basin in head Whale mixer tap/pull out shower head S/S galley sink Whale mixer tap Jabsco manual bilge pump in cockpit 3000 l/h Rule electric bilge pump 5.678 l/h Whale electric shower drain pump Jabsco marine toilet Racing type marelon seacocks and flush valves Fresh water fill on deck

Accommodation

All bulkheads and other interior components in PVC foam cored GRP composite White colored gelcoat surfaces with wooden trim for ease of maintenance, lightweight and modern appearance Honeycomb cored, satin varnished naturel oak wood veneer floor boards, cabin doors and cabinet doors Custom lightweight allov cabinets to match allov door frames, allov portlights trims Custom alloy handrails Southco alloy door handles High density foam cushions, Sunbrella upholstery Central salon area with settees port & starboard

Enclosed head to forward of mast, s/s hand basin, shower, china bowl, cabinet, wet locker Double berth cabin port & starboard aft, portlights for naturel light and fresh air Galley to port by companionway, s/s sink, cooker, refrigerator compartment Navigation station to starboard of companionway